



Series	GEL	Warranty	See Warranty Terms
Volts	2	BCI	2V OPzV
Cells	1		
Terminal Type	F10		
Included Hardware	Threaded Insert & Bolt		
Size & Thread	F10-M10		

Charge

Recommended Charge Current Capacity (String)	200 A
Self-Discharge Rate	Less than 2% per month at 25°C (77°F)
Internal Resistance	0.16 mΩ

Capacity

Capacity Affect by Temperature	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)
	105%	100%	89%	79%

Hour Rate	Capacity / AMP Hour	Current / AMPS
@ 100 Hour Rate	2927 AH	29.27 A
@ 20 Hour Rate	2437 AH	121.85 A
@ 10 Hour Rate	2160 AH	216 A

Specifications




SAI GLOBAL
ISO 9001
Quality

Weight	156 kg	344 lbs
Length	39.9 cm	15.71"
Width	21.4 cm	8.43"
Height Inc. Term.	79.9 cm	31.46"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process, battery components & electrolyte levels.

Container	ABS
Cover	ABS
Handles	None

Cycle Life vs. Depth of Discharge



Capacity vs. Temperature

